

# InsulSafe<sup>®</sup> SP

## Fiber Glass Blowing Insulation

### Certificate of Insulation

R-VALUE	BAG REQUIREMENTS	MAXIMUM COVERAGE	MINIMUM INITIAL INSTALLED THICKNESS	MINIMUM SETTLED THICKNESS
	BAGS PER 1000 SQ. FT./100 M <sup>2</sup> OF NET AREA	CONTENTS OF BAG SHOULD NOT COVER MORE THAN:	SHOULD NOT BE LESS THAN:	SHOULD NOT BE LESS THAN
<b>R</b>	<b>Number of Bags</b>	<b>sq. ft.</b>	<b>in.</b>	<b>in.</b>
R-60	31.4	31.9	22.00	22.00
R-49	25.2	39.7	18.50	18.50
R-44	22.4	44.6	16.75	16.75
R-38	19.1	52.5	14.50	14.50
R-30	14.9	67.1	11.75	11.75
R-19	9.3	107.4	7.75	7.75
R-13	6.2	161.7	5.25	5.25
R-11	5.3	190.5	4.50	4.50

This is to certify that CertainTeed InsulSafe<sup>®</sup> SP Fiber Glass Insulation has been installed to the manufacturer's recommendations and will achieve an R-Value\* of \_\_\_\_ using \_\_\_\_ bags of insulation to cover \_\_\_\_ square feet of area at a minimum installed thickness of \_\_\_\_ inches.

Street Address \_\_\_\_\_ City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_

Signed (Installer) \_\_\_\_\_ Date \_\_\_\_\_

Company \_\_\_\_\_ State License Number (if required) \_\_\_\_\_

City, State, Zip \_\_\_\_\_

InsulSafe SP is noncombustible, noncorrosive and inorganic. A product designed for today's safety standards and tomorrow's energy requirements. Keep this certificate with your other valuable papers. If you ever sell this property, this certificate should be passed on to the purchaser. \*The higher the R-Value, the greater the insulating power. Ask your seller for the fact sheet on R-Values.

